



S/N	Model No.	Product Picture	Specification	Packaging Specificatio	Weight/ KG	Solar panel configuration (optional)	
3	C1200	 	Model No.:	C1200	Packaging Dimensions (1 set): 360*280*310 mm	20KG	PV charging time/400W: 3.5 hours; AC charging time: 2 hours
			Host Size:	320*240*330			
			Rated Voltage of Battery:	25.6V 1280Wh/100%Full Capacity			
			Battery Type:	LiFePO ₄			
			Inverter (bidirectional):	1200W			
			Solar Input Voltage:	12V-60V			
			Maximum Solar Input Power:	400W			
			AC Input Rated Voltage:	230V			
			AC Input Voltage Range:	176V-264V			
			AC Input Maximum Power:	1200W			
			DC Output Voltage:	12V			
			DC Output 1 Maximum Power (Output Port XT60):	100W			
			DC Output 2 Maximum Power (Output Port 5521):	25W			
			DC Output 3 Maximum Power (Output Port 5521):	25W			
			DC Output 4 Maximum Power (Output Port 5521):	25W			
			DC Output 5 Maximum Power (Output Port 5521):	25W			
			USB Output:	DC5V 2 A (USB 2PCS)			
			AC Output Rated Voltage:	230V			
			AC Output Voltage Range:	220V-240V			
			AC Rated Output Maximum Power:	1200W			
			Relative Humidity:	10%-70%			
			Operating Temperature:	0-55°C			
			Protection Function:	Undervoltage, Overvoltage, Overcurrent, Short circuit			
			Cycle Life:	>1500 times			
			Warranty Period:	1 year			